

SGI UV 2000, UV 20: Big Brains for No-Limit Computing

The Most Powerful In-memory Supercomputers for
Compute-Intensive Workloads

Key Features

Scales up to 256 sockets and
64TB of coherent shared memory

SMP System utilizes
industry-standard Intel® Xeon®
processors and Linux® O/S

Builds on 20 years of in-memory
computing expertise



Solve the Most Demanding Compute-Intensive Problems

Part of the SGI UV server line for high performance in-memory computing, SGI UV 2000 and SGI UV 20 are advanced symmetric multiprocessing (SMP) systems designed for compute-intensive, fast algorithm workloads such as CAE, CFD, and scientific simulations.

SGI UV 2000 scales to truly extraordinary levels—up to 256 CPU sockets and 64TB of cache-coherent shared memory in a single system. Enabling such powerful in-memory computing capability is 6th generation SGI NUMalink® ASIC technology, providing extreme bandwidth, low latency network interconnects. Equipped with an integrated MPI Offload Engine, UV 2000 can also be leveraged for distributed applications and as a “super node” for clustered high performance computing (HPC) systems.

Designed for smaller, compute-intensive environments, SGI UV 20 is a 2U, 4-socket server providing up to 1.5TB of in-memory computing power.

Single System Simplicity with Extreme Scalability

The SGI UV 2000 features a modular chassis design that enables users to grow their system without adding complexity. A 10U chassis contains up to 16 sockets and 24 threads coupled with an All-to-All NUMalink network topology. By adding additional chassis (up to four per standard 19” rack) and using an Enhanced Hypercube topology, UV 2000 can scale up to 256 sockets and 4,096 threads, all operating as a single system. It's like running a giant workstation with lightning speed and maximum investment protection.

Flexible, Open, Energy Efficient

SGI UV 2000 is designed with optimum flexibility. Featuring Intel® Xeon® E5-4600 processors with eight DIMMs per socket, the system's x86 architecture delivers a high processor to memory ratio. NVIDIA® Quadro® and NVIDIA® Tesla® GPU accelerators and Intel® Xeon® Phi™ coprocessors can also be added. A choice of unmodified SUSE® Linux® Enterprise Server or Red Hat® Enterprise Linux operating systems make the UV 2000 ideal for standard ISV and open source applications as well custom codes. And SGI's innovative air or water cooling helps lower energy costs.

High Performance Storage with Fast Access

Industry-standard PCIe Gen3 expansion slots provide countless options for persistent storage with fast I/O, very-high bandwidth connectivity. For hardware, select from the entire SGI InfiniteStorage line of Storage Servers, RAID and tape libraries, as well as industry-standard 3rd party components. For storage software, leverage Intel® Enterprise Edition for Lustre, SGI CXFS™, or industry standard XFS® file systems, SGI XVM® volume management, SGI DMF™ tiered data management, and 3rd party backup solutions.



UV 2000, UV 20 Configuration Specifications

sgi.com/uv

System Components	
Processors	<ul style="list-style-type: none"> Intel® Xeon® processor E5-4600 v2 product family (2.4-3.3GHz)
Memory	<ul style="list-style-type: none"> 8, 16 or 32GB up to 1600 MT/s ECC DDR3 DIMMs
Disk Drives	<ul style="list-style-type: none"> 2.5" SATA, SAS HDD or SSD
Interconnect	<ul style="list-style-type: none"> NUMAlink® 6 (NL6; 6.7GB/s bidirectional)
Environmental	<ul style="list-style-type: none"> 68-77F (20-25C), 40-55% relative humidity (non-condensing)
Power	<ul style="list-style-type: none"> Single phase 30 amp or three phase (208, 400 or 480VAC) 60 amp
Cooling	<ul style="list-style-type: none"> Ambient air-cooled Optional water-cooled: water temp. 45-60F (7.2-15.6C)
Rack	
SGI Rack Dimensions (H x W x D)	<ul style="list-style-type: none"> 79.5" (42U) x 31.3" x 46.2" 201.9cm x 79.5cm x 117.3cm
Power	<ul style="list-style-type: none"> Single-phase 180-264VAC or three-phase 180-504VAC, 47-63Hz
Cooling	<ul style="list-style-type: none"> Open-looped airflow or optional water-cooled door
3rd party rack	<ul style="list-style-type: none"> Supported for UV 2000 configurations up to one rack scale
Blade Enclosure	
Dimensions (H x W x D)	<ul style="list-style-type: none"> 17.5" (10U) x 19" x 27" 44.5cm x 48.36cm x 68.68cm
Power	<ul style="list-style-type: none"> Three 12VDC 3037W, 200-240VAC or 277VAC input voltage (N+1)
Cooling	<ul style="list-style-type: none"> Nine hot-pluggable, 119mm, 12VDC axial cooling fans
Administrative Network	<ul style="list-style-type: none"> One Chassis Management Controller Two backplane connections
Compute Blade	
Dimensions (H x W x D)	<ul style="list-style-type: none"> 3.7" x 8.4" x 18.1" 9.4cm x 2.1cm x 46.0cm
2 CPU CPU + Accelerator	<ul style="list-style-type: none"> 2 Intel® Xeon® processor E5-4600 product family 1 Intel® Xeon® processor E5-4600 product family and 1 accelerator card
Memory	<ul style="list-style-type: none"> 8 DIMM Slots per Intel® Xeon® CPU
IO expansion options	<p>All IO slots are X16 Gen 3 capable. Options per blade include:</p> <ul style="list-style-type: none"> Base IO (specs below) Two 2.5" HDD or SSD slots Two low-profile slots One low-profile and one full-height, half-depth slot
Base I/O Features	<ul style="list-style-type: none"> Two 1.8" SATA SSD slots 3.0GB/s SAS controller with two X4 ports Two USB 2.0 ports Serial port VGA port Two Ethernet ports Dedicated Board Management Controller
System Expansion and Enhancement Options	<ul style="list-style-type: none"> NUMAlink 6 support for up to 16,384 socket system Support for Shared Memory up to 8 Petabytes Hard partitions maintain resilience while offering management flexibility
Large, Multi-partition UV2000 systems	
Graphics and Coprocessors	<ul style="list-style-type: none"> NVIDIA® Quadro® 5000/5200/6000 and NVIDIA® Tesla® K20x/K40 GPU computing accelerator Intel® Xeon® Phi™ coprocessor Scales to 32 accelerator devices within a single system image

UV 2000 System Management	
Board Management Controller	<ul style="list-style-type: none"> One per compute blade Monitors blade function Relays status or function data to management network
Chassis Management Controller	<ul style="list-style-type: none"> One per blade enclosure Controls master power to all compute blades Monitors power and blade enclosure environment
System Management Node	<ul style="list-style-type: none"> One per system Monitors and controls power and environmentals Manages hardware inventory and configuration, reports health status and failure analysis
SGI UV 20 4-way Server Specifications	
CPU	<ul style="list-style-type: none"> 4 Intel® Xeon® processor E5-4600 v2 product family 8, 10, or 12 core CPUs, 2.4-3.3 GHz
Memory	<ul style="list-style-type: none"> Up to 48 DIMM slots 4, 8, 16 or 32GB 1600/1866 MT/s ECC DDR3 DIMMs
Storage	<ul style="list-style-type: none"> Two 1.8" SSD plus up to 8 2.5" SAS, SATA HDD or SSD
IO Expansion	<ul style="list-style-type: none"> 4 external PCIe X16 Gen 3 slots, 2 internal IO module x 8
High End PCI	<ul style="list-style-type: none"> Up to 2 NVIDIA® Quadro®, NVIDIA® Tesla® computing accelerators and Intel® Xeon® Phi™ coprocessors
Dimensions	<ul style="list-style-type: none"> 2U, 17.24" (438mm) x 28" (712mm) x 3.43" (87.3mm)
Power	<ul style="list-style-type: none"> 2 1600W N+N redundant power supplies
Cooling	<ul style="list-style-type: none"> 11 40mm x 40mm x 56mm hot swap fans
Other	<ul style="list-style-type: none"> Base system includes integrated SAS, management controllers
Storage	
SGI InfiniteStorage™ Solutions	<ul style="list-style-type: none"> SGI RAID, NAS, SAN, Storage Servers, MAID and tape libraries
SGI InfiniteStorage Software	<ul style="list-style-type: none"> CXFS™, XFS®, DMF™, XVM®, and backup and restore solutions
Software Development	
Programming Languages and Debuggers	<ul style="list-style-type: none"> SGI Development Suite C & C++: Intel® C++ Compiler, GNU GCC Debuggers: Intel® Debugger included with Intel® compilers, GNU GDB, Rogue Wave Software® TotalView®, Allinea DDT Fortran: Intel® Fortran Compilers, GNU GCC Performance Analysis: Intel® VTune Amplifier XE, Intel® Trace Analyzer & Collector
Libraries	<ul style="list-style-type: none"> SGI MPI OpenMP included with Intel® compilers Intel® Math Kernel Library Intel® Parallel Building Blocks Intel® Integrated Performance Primitives Intel® MPI Library
System Software	
Operating Systems	<ul style="list-style-type: none"> SUSE® Linux® Enterprise Server 11 Red Hat® Enterprise Linux 6
SGI Linux System Software	<ul style="list-style-type: none"> SGI Foundation Software SGI Performance Suite SGI Management Suite
Virtualization Software	<ul style="list-style-type: none"> KVM

About SGI

SGI, the trusted leader in high performance computing (HPC), is focused on helping customers solve their most demanding business and technology challenges by delivering technical computing, Big Data analytics, cloud computing, and petascale storage solutions that accelerate time to discovery, innovation, and profitability. For more information please contact an SGI sales representative at 1-800-800-7441 or visit www.sgi.com/contactus.

Global Sales and Support: sgi.com/global

©2013–2014 Silicon Graphics International Corp. All rights reserved. SGI, UV, ICE, NUMAlink, CXFS, XFS, DMF, XVM and the SGI logo are registered trademarks or trademarks of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries. Intel, Xeon and the Intel Xeon logo are registered trademarks of Intel Corporation. All other trademarks are properties of their respective holders. 15042013 4377 15122014

